

Component Procedures: Hoses

Table of Contents

1. Vehicle Damage Warnings (Article 5408491)
2. All Technical Service Bulletins (itype_100)
3. Customer Interest Bulletins (itype_109)
4. Difficult steering (itype_130)
5. Safety (itype_107)

Component Procedures: Hoses

Vehicle Damage Warnings (Article 5408491)

SERVICE PRECAUTIONS

To prevent vehicle damage, always observe the following precautions:

-

After servicing a hose, check for leaks before and after test driving the vehicle.

Always use the correct size hose. Do not use standard sized hose in place of metric hose or vice versa.

Always use the correct type of hose. Never use vacuum hose in place of fuel hose. Never use

heater hose

in place of PCV hose.

When replacing hoses which are attached to the engine on one end and the frame or body on the other end, always leave sufficient length to compensate for engine movement (from torque).

All Technical Service Bulletins (itype_100)

Tsbs

- Recall - Loss Of Power Steering Assist (6010H, 2010/09/15)

- Power Steering - High Steering Effort/MIL/DTC C1099 (0600110, 2010/04/09)

Customer Interest Bulletins (itype_109)

Tsbs

- Power Steering - High Steering Effort/MIL/DTC C1099 (0600110, 2010/04/09)

Difficult steering (itype_130)

Tsbs

- Power Steering - High Steering Effort/MIL/DTC C1099 (0600110, 2010/04/09)

Safety (itype_107)

Tsbs

- Recall - Loss Of Power Steering Assist (6010H, 2010/09/15)