

# **Component Procedures: Center Mounted Brake Lamp**

## **Table of Contents**

1. High Mount Stop Lamp Replacement (Convertible) (Article 10405)
2. High Mount Stop Lamp Replacement (Coupe) (Article 10406)
3. High Mount Stop Lamp Replacement (ZL1) (Article 10407)

# Component Procedures: Center Mounted Brake Lamp

## High Mount Stop Lamp Replacement (Convertible) (Article 10405)

Callout Component Name

Preliminary Procedure Remove the rear window upper reveal molding. Refer to Rear Window Upper Reveal Molding Replacement .

Preliminary Procedure

Remove the rear window upper reveal molding. Refer to Rear Window Upper Reveal Molding Replacement .

1 High Mount Stop Lamp Screw (Qty: 2) Caution: Refer to Fastener Caution . Procedure When installing CHMSL replace all seals on the push in retainers to prevent water entry.

Procedure

When installing CHMSL replace all seals on the push in retainers to prevent water entry.

2 High Mount Stop Lamp Assembly Procedure Water test vehicle to check for any leaks.

Water test vehicle to check for any leaks.

## High Mount Stop Lamp Replacement (Coupe) (Article 10406)

Callout Component Name

Preliminary Procedures Remove the rear window panel trim. Refer to Rear Window Panel Trim Replacement . Pull back the window panel acoustic trim filler in order to access the high mount stop lamp . Disengage the high mount stop lamp electrical connector from the rear window trim panel. Pull the high mount stop lamp from the rear window panel trim.

Preliminary Procedures

- Remove the rear window panel trim. Refer to Rear Window Panel Trim Replacement .
- Pull back the window panel acoustic trim filler in order to access the high mount stop lamp .
- Disengage the high mount stop lamp electrical connector from the rear window trim panel.
- Pull the high mount stop lamp from the rear window panel trim.

1 High Mount Stop Lamp Tip: The high mount stop lamp is serviced as one part.

## High Mount Stop Lamp Replacement (ZL1) (Article 10407)

Callout Component Name

Preliminary Procedure Remove the rear end spoiler. Refer to Rear End Spoiler Replacement .

Preliminary Procedure

Remove the rear end spoiler. Refer to Rear End Spoiler Replacement .

1 Rear End Spoiler Bolt (Qty: 2) Caution: Refer to Fastener Caution . Remove caps from each end of the high mount stop lamp to access bolts.

2 High Mount Stop Lamp Procedures Using a suitable flat bladed plastic tool separate high mount stop lamp from rear end spoiler. Disconnect the electrical harness connector and feed through rear end spoiler to fully separate high mount stop lamp from rear end spoiler. Clean area with a 50/50 solution by volume of isopropyl alcohol and clean drinkable water. Dry area with a clean lint-free cloth.

Procedures

- Using a suitable flat bladed plastic tool separate high mount stop lamp from rear end spoiler.
- Disconnect the electrical harness connector and feed through rear end spoiler to fully separate high mount stop lamp from rear end spoiler.
- Clean area with a 50/50 solution by volume of isopropyl alcohol and clean drinkable water.
- Dry area with a clean lint-free cloth.