

Component Procedures: Spoiler

Table of Contents

1. Rear End Spoiler Replacement (Article 10011)
2. Rear End Spoiler Replacement (ZL1) (Article 10012)
3. All Technical Service Bulletins (itype_100)

Component Procedures: Spoiler

Rear End Spoiler Replacement (Article 10011)

Callout Component Name

Preliminary Procedures Open the rear compartment lid . Remove the rear compartment lid carpet . Refer to Rear Compartment Lid Carpet Replacement .

Preliminary Procedures

- Open the rear compartment lid .
- Remove the rear compartment lid carpet . Refer to Rear Compartment Lid Carpet Replacement .

1 Rear End Spoiler Nut (Qty: 6) Caution: Refer to Fastener Caution . Tighten 6 Nm(53 lb in)

6 Nm(53 lb in)

2 Rear End Spoiler Assembly Procedures Transfer the radio control module, if equipped. Position the new spoiler to the rear compartment lid stud holes. Raise the rear compartment lid. Install and secure all nuts.

Procedures

- Transfer the radio control module, if equipped.
- Position the new spoiler to the rear compartment lid stud holes.
- Raise the rear compartment lid.
- Install and secure all nuts.

Rear End Spoiler Replacement (ZL1) (Article 10012)

Callout Component Name

Preliminary Procedure Open the deck lid

Preliminary Procedure

1 Rear End Spoiler Nut (Qty: 4) Caution: Refer to Fastener Caution .

2 Rear End Spoiler Retainer (Qty: 2)

3 Rear End Spoiler Retainer (Qty: 2) Note: Rear end spoiler retainer breaks on removal, replace as needed.

4 Rear End Spoiler Procedure Use a suitable plastic flat bladed tool to release the rear end spoiler retainers from the deck lid .

Procedure

All Technical Service Bulletins (itype_100)

Tsbs

- GM Accessory and Camaro Transformer High Wing Spoiler Center High Mount Stop Lamp (CHMSL) Cracking Around Fasteners (PI0685B, 2013/04/29)