

# **Component Procedures: Heat Shield**

## **Table of Contents**

1. Exhaust Muffler Front Heat Shield Replacement (Left) (Article 11985)
2. Exhaust Muffler Front Heat Shield Replacement (Right) (Article 11986)
3. Exhaust Muffler Intermediate Heat Shield Replacement (Article 11987)

# Component Procedures: Heat Shield

## Exhaust Muffler Front Heat Shield Replacement (Left) (Article 11985)

Callout Component Name

Warning: Refer to Exhaust Service Warning . Warning: Refer to Eye Protection Warning . Preliminary Procedures Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle . Remove the left catalytic converter . Refer to Catalytic Converter Replacement - Left Side .

Preliminary Procedures

- Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle .

- Remove the left catalytic converter . Refer to Catalytic Converter Replacement - Left Side .

1 Exhaust Front Heat Shield – Left Fastener (Qty: 3) Caution: Refer to Fastener Caution . Tighten 6 Nm (53 lb in)

6 Nm (53 lb in)

2 Exhaust Front Heat Shield – Left

## Exhaust Muffler Front Heat Shield Replacement (Right) (Article 11986)

Callout Component Name

Warning: Refer to Exhaust Service Warning . Warning: Refer to Eye Protection Warning . Preliminary Procedures Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle . Remove the right catalytic converter . Refer to Catalytic Converter Replacement - Left Side .

Preliminary Procedures

- Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle .

- Remove the right catalytic converter . Refer to Catalytic Converter Replacement - Left Side .

1 Exhaust Front Heat Shield – Right Fastener (Qty: 3) Caution: Refer to Fastener Caution . Tighten 6 Nm (53 lb in)

6 Nm (53 lb in)

2 Exhaust Front Heat Shield – Right

## Exhaust Muffler Intermediate Heat Shield Replacement (Article 11987)

Callout Component Name

Preliminary Procedures Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle . Partially lower and support the exhaust system . Refer to Exhaust Muffler with Resonator, Exhaust, and Tail Pipe Replacement .

Preliminary Procedures

- Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle .

- Partially lower and support the exhaust system . Refer to Exhaust Muffler with Resonator, Exhaust, and Tail Pipe Replacement .

1 Nut (Qty: 2) Caution: Refer to Fastener Caution . Note: Tighten the nuts until secure.

2 Exhaust Heat Shield Procedure Reposition the differential cooler pipes as necessary, if equipped.

Procedure

Reposition the differential cooler pipes as necessary, if equipped.