

Component Procedures: Sun Shade

Table of Contents

1. Sunroof Sunshade Replacement (Article 13167)

Component Procedures: Sun Shade

Sunroof Sunshade Replacement (Article 13167)

Removal Procedure

- Cycle the sunroof window to the partially open position. [Click for full-size image](#)
- Pull downward on the sunshade . Cycle the sunroof to full open position. Disengage the sunshade from the sunroof glass panel .
- Depress the panel (2) to one side of the track. [Click for full-size image](#)
- Carefully arch the sunshade upward at the forward center edge.
- Carefully lift the front edge (1) of the sunshade upward out of the track.
- Slightly rotate the sunshade panel in order to remove the panel from the track. [Click for full-size image](#)
- Carefully remove the sunshade panel upward from the sunroof frame .

Installation Procedure

- Position rear edge of the sunshade panel to the track. [Click for full-size image](#)
- Ensure that the slider pad at the rear is positioned into the track.
- Depress the rear slider pad on the opposite side of the sunshade panel and release it into the track.
- Install the front edge (1) of the sunshade panel slider pad into the track. [Click for full-size image](#)
- Arch the forward edge of the sunshade in order to insert it into sunshade track.
- Install the slider pad into the track and release.
- Slide the sunshade panel forward and rearward to ensure free operation is present.
- With the sunshade partially open, pull downward on the sunshade. Cycle the sunroof to the vent position, allowing the glass panel to travel past the sunshade front edge.
- Release the sunshade. Cycle the sunroof to the open position. Inspect for proper engagement of the sunroof glass panel and the sunshade panel. [Click for full-size image](#)