

Component Procedures: Exhaust Pipe/Muffler Hanger

Table of Contents

1. Underbody Brace Replacement (Convertible only) (Article 12002)
2. Underbody Brace Replacement (Coupe and Convertible) (Article 12003)

Component Procedures: Exhaust Pipe/Muffler Hanger

Underbody Brace Replacement (Convertible only) (Article 12002)

Callout Component Name

Warning: Refer to Exhaust Service Warning . Warning: Refer to Eye Protection Warning . Preliminary Procedure

Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle .

Preliminary Procedure

Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle .

1 Underbody Brace Fastener (Qty: 8) Caution: Refer to Fastener Caution . Tighten 58 Nm (43 lb ft)

58 Nm (43 lb ft)

2 Underbody Brace

Underbody Brace Replacement (Coupe and Convertible) (Article 12003)

Callout Component Name

Warning: Refer to Hot Exhaust System Warning . Warning: Refer to Exhaust Service Warning . Preliminary

Procedure Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle .

Preliminary Procedure

Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle .

1 Underbody Brace Bolt (Qty: 4) Caution: Refer to Fastener Caution . Tighten 58 Nm (43 lb ft)

58 Nm (43 lb ft)

2 Underbody Brace