

Component Procedures: Front Door Panel

Table of Contents

1. Front Side Door Trim Panel Replacement (Article 10078)

Component Procedures: Front Door Panel

Front Side Door Trim Panel Replacement (Article 10078)

Callout Component Name

Preliminary Procedure Remove the radio front side door upper speaker grille . Refer to Radio Front Side Door Upper Speaker Grille Replacement .

Preliminary Procedure

Remove the radio front side door upper speaker grille . Refer to Radio Front Side Door Upper Speaker Grille Replacement .

1 Front Side Door Inside Handle Bolt Finish Cap Procedure Use a small flat bladed tool at the front edge of the cover to aid in removal.

Procedure

Use a small flat bladed tool at the front edge of the cover to aid in removal.

2 Front Side Door Trim Fastener (Qty: 4) Caution: Refer to Fastener Caution . Tighten 2 Nm (18 lb in)

2 Nm (18 lb in)

3 Front Side Door Pull Cup Fastener Procedure Remove the front side pull cup liner to access the fastener.

Tighten 2 Nm (18 lb in)

Remove the front side pull cup liner to access the fastener.

4 Front Side Door Trim Panel Procedure Use a door trim tool or equivalent to aid in the removal of the door trim. Disconnect the inside handle release cable from the trim panel. Disconnect the electrical connectors.

Transfer parts as required.

- Use a door trim tool or equivalent to aid in the removal of the door trim.
- Disconnect the inside handle release cable from the trim panel.
- Disconnect the electrical connectors.
- Transfer parts as required.