

Component Procedures: Front Fender Liner

Table of Contents

1. Front Wheelhouse Liner Replacement (Base, RS, SS) (Article 10209)
2. Front Wheelhouse Liner Replacement (ZL1) (Article 10210)
3. Front Wheelhouse Panel Extension Replacement (Article 10211)

Component Procedures: Front Fender Liner

Front Wheelhouse Liner Replacement (Base, RS, SS) (Article 10209)

Callout Component Name

Preliminary Procedure Remove the tire and wheel assembly. Refer to Tire and Wheel Removal and Installation .

Preliminary Procedure

Remove the tire and wheel assembly. Refer to Tire and Wheel Removal and Installation .

1 Front Wheelhouse Liner Screw (Qty: 5) Caution: Refer to Fastener Caution . Tighten 3 Nm (27 lb in)
3 Nm (27 lb in)

2 Front Wheelhouse Liner Push-In Retainer (Qty: 5)

3 Front Wheelhouse Liner

Front Wheelhouse Liner Replacement (ZL1) (Article 10210)

Callout Component Name

Preliminary Procedures Remove the tire and wheel assembly. Refer to Tire and Wheel Removal and Installation .

Remove the front bumper valance panel. Refer to Front Bumper Valance Panel Replacement .

Preliminary Procedures

- Remove the tire and wheel assembly. Refer to Tire and Wheel Removal and Installation .

- Remove the front bumper valance panel. Refer to Front Bumper Valance Panel Replacement .

1 Front Wheelhouse Liner Screw (Qty: 12) Caution: Refer to Fastener Caution . Tighten 3 Nm (27 lb in)
3 Nm (27 lb in)

2 Front Wheelhouse Liner Push-In Retainer (Qty: 5)

3 Front Wheelhouse Liner

Front Wheelhouse Panel Extension Replacement (Article 10211)

Callout Component Name

Preliminary Procedure Remove the front wheelhouse liner. Refer to Front Wheelhouse Liner Replacement .

Preliminary Procedure

Remove the front wheelhouse liner. Refer to Front Wheelhouse Liner Replacement .

1 Front Bumper Valance Panel Bolt Caution: Refer to Fastener Caution .

2 Front Wheelhouse Panel Extension Warning: Refer to Eye Protection Warning . Procedure Remove rivets. Using a suitable flat-bladed plastic tool separate front wheelhouse panel extension from front bumper fascia . Clean front wheelhouse panel extension and front bumper fascia with a 50/50 solution by volume of isopropyl alcohol and clean drinkable water. Dry with a clean lint-free cloth.

Procedure

- Remove rivets.

- Using a suitable flat-bladed plastic tool separate front wheelhouse panel extension from front bumper fascia .

- Clean front wheelhouse panel extension and front bumper fascia with a 50/50 solution by volume of isopropyl alcohol and clean drinkable water.

- Dry with a clean lint-free cloth.