

Component Procedures: Front Door Hinge

Table of Contents

1. Front Side Door Upper Hinge and Lower Hinge Replacement (Article 10115)

Component Procedures: Front Door Hinge

Front Side Door Upper Hinge and Lower Hinge Replacement (Article 10115)

Callout Component Name

1 Front Side Door Upper Hinge to Body Bolts (Qty: 2) Caution: Refer to Fastener Caution . Procedures Before removing the door, apply a double layer of masking tape around the perimeter of the painted surfaces. Mark the location of the hinge being removed. Remove the front wheelhouse liner. Refer to Front Wheelhouse Liner Replacement Support the door before removing the hinge bolts. Tighten 34 Nm (25 lb ft)

Procedures

- Before removing the door, apply a double layer of masking tape around the perimeter of the painted surfaces.
- Mark the location of the hinge being removed.
- Remove the front wheelhouse liner. Refer to Front Wheelhouse Liner Replacement
- Support the door before removing the hinge bolts.

34 Nm (25 lb ft)

2 Front Side Door Upper Hinge to Door Bolts (Qty: 2) Tighten 10 Nm (89 lb in)

10 Nm (89 lb in)

3 Front Side Door Upper Hinge

4 Front Side Door Lower Hinge to Body Bolts (Qty: 2) Tighten 34 Nm (25 lb ft)

5 Front Side Door Lower Hinge to Door Bolts (Qty: 2) Tighten 10 Nm (89 lb in)

6 Front Side Door Lower Hinge