

Component Procedures: Windshield Moulding / Trim

Table of Contents

1. Windshield Side Garnish Molding Replacement (Convertible) (Article 10101)
2. Windshield Side Garnish Molding Replacement (Coupe) (Article 10102)

Component Procedures: Windshield Moulding / Trim

Windshield Side Garnish Molding Replacement (Convertible) (Article 10101)

Callout Component Name

Preliminary Procedure Place the folding top assembly in a full down position to allow access to the windshield side garnish molding.

Preliminary Procedure

Place the folding top assembly in a full down position to allow access to the windshield side garnish molding.

1 Windshield Side Garnish Molding Assembly Procedure Starting at the top, gently pull on the garnish molding to disengage the clips. Disconnect electrical connector. Garnish clips must be seated in roof front header garnish molding lower prior to installing sealing clips. Tabs to be fully seated in instrument panel trim pad.

Procedure

- Starting at the top, gently pull on the garnish molding to disengage the clips.
- Disconnect electrical connector.
- Garnish clips must be seated in roof front header garnish molding lower prior to installing sealing clips.
- Tabs to be fully seated in instrument panel trim pad.

Windshield Side Garnish Molding Replacement (Coupe) (Article 10102)

Removal Procedure

- Disable the SIR system. Refer to SIR Disabling and Enabling .
- Remove the windshield side garnish molding assembly (1) from the clip retainers on the upper side rail.

Click for full-size image

- Remove the retainer (1) from the bodyside. Click for full-size image
- Slide a small flat-bladed tool on the outboard side to disengage the center retainer (2), maintain pressure on the tab.
- Slide another small flat-bladed tool on the opposite side of the retainer to depress the outer tabs (3), maintain pressure on the tabs.
- Rotate the retainer out parallel to the upper reinforcement body hinge pillar.

Installation Procedure

- Install the one-piece service closed retainer (2) to the windshield side garnish molding assembly (1). Click for full-size image
- Install the windshield side garnish molding assembly (1). Click for full-size image