

Component Procedures: Back Window Glass Moulding / Trim

Table of Contents

1. Rear Window Upper Reveal Molding Replacement (Article 10278)

Component Procedures: Back Window Glass Moulding / Trim

Rear Window Upper Reveal Molding Replacement (Article 10278)

Callout Component Name

1 Rear Window Upper Reveal Molding Retainer (Qty:4)

2 Rear Window Upper Reveal Molding Procedure Open the rear compartment lid in order to access the rear lamp electrical harness. Disengage the electrical grommet from the rear window drain panel. Disconnect the electrical connector from the rear lamp electrical harness. Apply tape around the outside perimeter of the reveal molding. Using a plastic tool, apply adequate pressure upward to release the retainers and reveal molding from the vehicle. Replace all broken retainers Transfer the high mount stop lamp. Tip: Using a suitable tool, insert the grommet into the rear window drain panel.

Procedure

- Open the rear compartment lid in order to access the rear lamp electrical harness.
- Disengage the electrical grommet from the rear window drain panel.
- Disconnect the electrical connector from the rear lamp electrical harness.
- Apply tape around the outside perimeter of the reveal molding.
- Using a plastic tool, apply adequate pressure upward to release the retainers and reveal molding from the vehicle.
- Replace all broken retainers
- Transfer the high mount stop lamp.